



M206

MULTISERVICE COMPACT TERMINAL

The M206 is a terminal **designed to provide traditional and innovative web services** in point-of-sale environments.

Lottery sales and payment of winning ticket, paying utility bills, recharge of pre-paid cards, and signing contracts are just some of the services the M206 terminal can be used for.

As the M206 terminal supports a second display with an **HDMI interface**, it can also be used to deliver video **content**.

As a compact device (A4 footprint) M206 is the ideal tool for any Gaming and Retail Organizations, Banks as well as Public Authorities.

SCANNER FOR PLAY SLIPS, PAYMENT FORMS, DOCUMENTS

THERMAL RECEIPT PRINTER WITH PAPER CUTTER

HIGH PROCESSING PERFORMANCE

TOUCH SCREEN OPERATOR DISPLAY

ABLE TO MANAGE LARGE GRAPHIC CUSTOMER DISPLAY

BUILT-IN CUSTOMER DISPLAY

BUILT-IN WEBCAM AND MICROPHONE



TILT-ADJUSTABLE DISPLAY for standing or seated users



EASY REPLACEMENT OF PAPER ROLLS



AUTOMATIC SCANNER ACTIVATION when a document is inserted

TECHNICAL SPECIFICATIONS

BASE UNIT

Processing unit

- Intel Main board std format mini-ITX
- CPU Atom® Dual Core™ N2800 1,6 GHz, fanless-cooled
- Full HD Graphic 1080
- Dual independent display support
- Intel HD audio
- RAM: Memory 2 GB (expandable to max. 4 GB)
- 3 PCI express expansion slots
- 1 LAN port 10/100/1000 Mbits/s
- 4 (back) + 1 (front) USB ports for external peripherals connections
- 1 HDMI and 1 VGA ports for external display connections (up 1920 x 1200)

Mass storage

- Hard Disk Unit with at least 250 GB (reliability 24hrs / 24x7days / 7)
- Solid Disk State with at least 32 GB

Operating system

- Microsoft® Windows 7
- Linux

PERIPHERALS

Touch screen operator display

- 10" colour LCD LED TFT wide screen
- Resolution: 1024 x 600 pixel
- Resistive touch screen, 5 wires
- Tilt angle display

Keyboard (option)

- Built-in, 20 keys
- Layout with numerical pad and functional keys

Scanner (option)

- Optical sensor with RGB colour technology
- Documents width up to 120 mm
- Reading width up to 108 mm
- Resolution up to 300 x 300 dpi
- Resolution up to 300 x 300 dpi

Webcam (option)

- Resolution: 2 Mpixel (1600 x 1200 at 24 bit/color)
- Frame rate up to 30 fps (at res. 640 x 480)

Microphone (option)

Two channel microphone (right/left)

External power supply

- Input voltage: 100 - 240 Vac (50-60 Hz)
- Output voltage: 24V 7.5A

Thermal printer

- Paper width: 82.5 mm
- Paper diameter: 100 mm
- Easy paper roll loading
- Printing speed: 200 mm/s
- Resolution 203 dpi
- Autocutter with partial and total cut

Audio Inputs

Frontal jack for external microphone

Audio outputs

- 2 frontal speakers (right/left) 2 W/channel
- Frontal jack for external speakers

Multicard reader (option)

SD / MMC slot (internal)

Optional devices

- Bar code reader 1D / 2D
- Customer display 12.1" VGA
- Customer display 2 x 16 LED back light
- Pin-pad for operator identification, magnetic card/smart card reading, encryption functions
- Large customer display (HDMI or VGA)

GENERAL

Dimensions (WxDxH)

226 x 317 x 348 mm (with LCD angle at 55°; display width 273 mm)

Weight

~ 6 kg

Certifications

CE, RoHS, REACH

Operating temperature

+ 10 °C / + 40 °C

Storage temperature

- 5 °C / + 45 °C

Product performances are referred to an appropriate use under optimal conditions. With the right to change technical specifications. The registered trademarks are the property of their respective owners. M206 is distributed by Olivetti S.p.A. (10/12) - Code: 700222-03